

## ClearDesign DesignServer (Small)

### 3000049031748.1 - Dell OEM PowerEdge T140

210-AQZN - 1 OEM PowerEdge T140 Server 210-AQZN - 1  
321-BDVW - 1 3.5" Chassis up to 4 Cabled Hard Drives 321-BDVW - 1  
325-BDEP - 1 Brand/Bezel, OEM PowerEdge T140 325-BDEP - 1  
329-BDXC - 1 PowerEdge T140 Motherboard 329-BDXC - 1  
332-1286 - 1 US Order 332-1286 - 1  
338-BQBI - 1 Intel Xeon E-2144G 3.6GHz, 8M cache, 4C/8T, turbo (71W) 338-BQBI - 1  
340-CHNX - 1 OEM PowerEdge T140 Shipping 340-CHNX - 1  
340-CHNY - 1 OEM PowerEdge T140 Shipping Material, DAO 340-CHNY - 1  
370-AAIP - 1 Performance Optimized 370-AAIP - 1  
370-AEKL - 1 16GB 2666MT/s DDR4 ECC UDIMM 370-AEKL - 1  
370-AEKM - 1 2666MT/s UDIMMs 370-AEKM - 1  
379-BCQY - 1 iDRAC Group Manager, Disabled 379-BCQY - 1  
379-BCRG - 1 iDRAC, Factory Generated Password 379-BCRG - 1  
384-BBBL - 1 Performance BIOS Settings 384-BBBL - 1  
385-BBLD - 1 iDrac9, Basic 385-BBLD - 1  
400-AFXX - 2 1TB 7.2K RPM SATA 6Gbps 3.5in Cabled Hard Drive 400-AFXX - 2  
405-AANS - 1 PERC H330 RAID Controller, Adapter, Full Height 405-AANS - 1  
412-AAQD - 1 Heatsink for 80W or less CPU 412-AAQD - 1  
429-AAQM - 1 DVD ROM SATA Internal 429-AAQM - 1  
450-AALV - 1 NEMA 5-15P to C13 Wall Plug, 125 Volt, 15 AMP, 10 Feet (3m), Power Cord, North America 450-AALV - 1  
461-AADZ - 1 No Trusted Platform Module 461-AADZ - 1  
542-BBBP - 1 On-Board LOM 542-BBBP - 1  
605-BBFN - 1 No Media Required 605-BBFN - 1  
619-ABVR - 1 No Operating System 619-ABVR - 1  
631-AACK - 1 No Systems Documentation, No OpenManage DVD Kit 631-AACK - 1  
709-BBFJ - 1 Basic Next Business Day 15Months 709-BBFJ - 1  
780-BCDN - 1 RAID 1 780-BCDN - 1  
800-BBDM - 1 UEFI BIOS Boot Mode with GPT Partition 800-BBDM - 1  
865-BBQM - 1 ProSupport 4HR Mission Critical Initial, 15 Month(s) 865-BBQM - 1  
865-BBQN - 1 ProSupport 4HR Mission Critical Extension, 24 Month(s) 865-BBQN - 1  
900-9997 - 1 On-Site Installation Declined 900-9997 - 1  
973-3700 - 1 Enterprise Program Management Support 973-3700 - 1