

ClearDesign DesignServer (Large)

3000049032706.1 - Dell OEM PowerEdge T440

210-ANMM - 1 OEM PowerEdge T440 Server 210-ANMM - 1
384-BCFT - 1 PowerEdge T440 MLK Motherboard 384-BCFT - 1
461-AADZ - 1 No Trusted Platform Module 461-AADZ - 1
321-BCVN - 1 Chassis with up to 8, 3.5" Hot Plug Hard Drives, Tower Configuration 321-BCVN - 1
340-BVTS - 1 OEM PowerEdge T440 Shipping 340-BVTS - 1
343-BBHH - 1 OEM PowerEdge T440 Shipping Material, DAO 343-BBHH - 1
338-BSWX - 1 Intel Xeon Silver 4208 2.1G, 8C/16T, 9.6GT/s, 11M Cache, Turbo, HT (85W) DDR4-2400 338-BSWX - 1
374-BBBX - 1 No Additional Processor 374-BBBX - 1
412-AAJW - 1 Standard Heat Sink for Less = 150W 412-AAJW - 1
370-ADNU - 1 2666MT/s RDIMMs 370-ADNU - 1
370-AAIP - 1 Performance Optimized 370-AAIP - 1
780-BCDN - 1 RAID 1 780-BCDN - 1
405-AANS - 1 PERC H330 RAID Controller, Adapter, Full Height 405-AANS - 1
420-6320 - 1 No Operating System 420-6320 - 1
421-5736 - 1 No Media Required 421-5736 - 1
385-BBLD - 1 iDrac9, Basic 385-BBLD - 1
379-BCQY - 1 iDRAC Group Manager, Disabled 379-BCQY - 1
379-BCRG - 1 iDRAC, Factory Generated Password 379-BCRG - 1
542-BBBP - 1 On-Board LOM 542-BBBP - 1
429-ABCK - 1 DVD ROM, SATA, Internal 429-ABCK - 1
450-AGRE - 1 Dual, Hot-plug, Redundant Power Supply (1+1), 495W 450-AGRE - 1
325-BCSB - 1 Brand/Bezel, OEM PowerEdge T440 325-BCSB - 1
384-BBBL - 1 Performance BIOS Settings 384-BBBL - 1
800-BBDM - 1 UEFI BIOS Boot Mode with GPT Partition 800-BBDM - 1
770-BBCR - 1 No Rack Rails, No Cable Management Arm, No Casters 770-BBCR - 1
631-AACK - 1 No Systems Documentation, No OpenManage DVD Kit 631-AACK - 1
332-1286 - 1 US Order 332-1286 - 1
709-BBFI - 1 Basic Next Business Day 15Months 709-BBFI - 1
865-BBQK - 1 ProSupport Next Business Day Onsite Service Initial, 15 Month(s) 865-BBQK - 1
865-BBQL - 1 ProSupport Next Business Day Onsite Service Extension, 24 Month(s) 865-BBQL - 1
900-9997 - 1 On-Site Installation Declined 900-9997 - 1
370-ADND - 1 16GB RDIMM, 2666MT/s, Dual Rank 370-ADND - 1
400-ASNK - 2 4TB 7.2K RPM NLSAS 12Gbps 512n 3.5in Hot-plug Hard Drive 400-ASNK - 2
450-AALV - 2 NEMA 5-15P to C13 Wall Plug, 125 Volt, 15 AMP, 10 Feet (3m), Power Cord, North America 450-AALV - 2
973-3700 - 1 Enterprise Program Management Support 973-3700 - 1